

securosys



The affordable hardware security module Primus HSM E-Series

- Market-leading price-performance ratio
- HSM Network Appliance as a replacement for PCIe cards
- Simple setup, configuration, and maintenance
- Tamper protection during transport, storage, and operation
- Scalable and flexible partitionable to your needs
- Designed, developed, and manufactured in Switzerland

The E-Series of our Primus HSM offers high performance at an outstanding price. Connecting the devices to existing systems is just as easy as commissioning.

Different performance classes

The E-Series is available in various performance classes: E20, E60 and E150. It can be configured via the serial port or over the network with our Decanus remote terminal.

Applications

The devices of the E-Series are very versatile. Built as network appliances, they lack the disadvantages of PCIe-based solutions like software dependence of PCIe host systems and the host system itself. The E-Series is ideally suited to secure financial transactions such as EBICS and PCI, access to the cloud (CASB), key management in the PKI environment, or to protect blockchain systems, crypto assets management.

Functions

The devices generate encryption keys, store and manage the distribution of these keys. Besides key management, they also perform authentication and encryption tasks. Multiple Primus HSM can be grouped together to support redundancy and load balancing. Each Primus HSM can also be partitioned for multiple users (multi-tenancy). Primus supports symmetric (AES, Camellia), asymmetric (RSA, ECC, Diffie-Hellman), and hashing (SHA-2, SHA-3) cryptographic algorithms. They can be seamlessly and easily integrated into any network environment. The Primus E-Series HSM can be remote controlled with our Decanus Remote Control Terminal.

Security Features

Security architecture

- Multilevel security architecture
- Intern hardware supervision for error-free operations

Encryption/Authentication (extract)

- 128/192/256-Bit AES
with GCM-, CTR-, ECB-, CBC-, MAC-mode
- Camellia, 3DES (legacy), ChaCha20-Poly1305
- RSA 1024-8192, DSA 1024-8192
- ECDSA 224-521, GF(P) arbitrary curves (NIST, Brainpool,...)
- ED25519, Curve25519
- Diffie-Hellman 1024-4096, ECDH
- SHA-2/SHA-3 (224-512), SHA-1, RIPEMD-160, Keccak, HMAC, CMAC, GMAC, Poly1305
- Upgradeable to quantum computer-resistant algorithms

Key Generation

- Two hardware true random number generators (TNRG)
- NIST SP800-90 compatible random number generator

Key Management

- Key capacity: up to 6 GB
- Ultra-secure vault for long term keys and certificates
- Up to 50 partitions @ 120 MB capacity

Operation

- Unlimited number of backups
- Number of client connections not restricted

Anti Tampering Mechanisms

- Several sensors to detect unauthorized access
- Active destruction of key material and sensitive data on tamper
- Transport and multi-year storage tamper protection by digital seal

Firmware

- Local firmware update on device or optionally on Decanus remote

Identity based authentication

- Multiple security officers (2 out of n)
- Identification based on Smartcard and PIN using Decanus remote, or through virtual Smartcard

Networking Features

Software integration

- JCE/JCA Provider
- PKCS#11, P11-Kit, OpenSSL, Apache, Nginx
- Microsoft CNG
- REST (TSB Module)

Network Management

- IPv4/IPv6
- Monitoring and logging (SNMPv2, syslog)

Device Management

- Local configuration (console)
- Remote configuration (Decanus)
- Integrated logging
- Firmware update
- Enhanced diagnostic functions

Technical Data

Performance (per second, concurrent)

	RSA 4096	ECC 256	ECC 521	AES 256
E150	150	1100	180	1500
E60	60	700	120	600
E20	20	350	60	200

Power

- Power supply: 100 ... 240 V AC, 50 ... 60 Hz
- Power dissipation: 30 W (typ), 50 W (max)
- Backup lithium battery: Lithium Thionyl Chloride 0.65g Li, IEC 60086-4, UL 1642, 3.6V

Interfaces

- 4 Ethernet RJ-45-ports with 1 Gbit/s (rear)
- 1 RS-232 management port (rear)
- 1 USB management port (rear)

Controls

- Console interface
- 4 LEDs for system and interface status (multicolored)
- Optional Decanus Remote Control Terminal

Environmental Test Specifications (target)

- EMV/EMC: EN 55022, EN 55024, FCC Part 15 Class B
- Safety: IEC 62386-1

Specifications

- Temperature ranges (IEC 60068-2-1 Ad, IEC 60068-2-2 Bd): storage -25 ... +70 °C; operation 0 ... +40 °C, recommended +1 ... 30 °C
- Humidity (IEC 60068-2-78 Cab): 40 °C, 93% RH, non-condensing
- MTBF (RIAC-HDBU-217Plus) at $t_{amb}=25$ °C: 80 000 h
- Dimensions (w×h×d) 417 x 44 x 365 mm (1U 19" EIA standard rack)
- Weight 5,8 kg


Certification

- FIPS140-2 Level 3
- CC EN 419221-5 eIDAS protection profile
- CE, FCC, UL

HEADQUARTER
Securosys SA
Max-Högger-Strasse 2
8048 Zürich
SCHWEIZ
+41 44 552 31 00
info@securosys.com
www.securosys.com

GERMANY & EU
Securosys
Deutschland GmbH
Darrestrasse 9
87600 Kaufbeuren
DEUTSCHLAND
+49 8341 438620
info@securosys.de
www.securosys.de

APAC
Securosys
Hong Kong Ltd.
Unit 704B Sunbeam Centre
27 Shing Yip Street
Kwun Tong
Hong Kong
+852 8193 1646
info-apac@securosys.com
www.securosys.com



Front



Rear

We strive to continuously improve our offerings and therefore reserve the right to change specifications without notice.
Designed and manufactured in Switzerland.

Copyright ©2023 Securosys SA. All rights reserved. EV1.9.